

PROSTREET 2026

Engine

1. No cubic inch limit.
2. Any aluminum cylinder head permitted.
3. Aluminum blocks are permitted. Trucks with aluminum blocks must have 100 lbs. of weight in the engine bay that is visible to tech inspector.
4. Engine block must have stock bore spacing.
5. Single naturally aspirated carburetor only. No tunnel rams or sheet metal intakes.
6. Any engine allowed with any make body.
7. Rear of block must be 12 inches behind the center of the front axle tube.

Suspension/Drive Train

1. No larger than 1 ton drive line.
2. OEM frame rail only.
3. Wheelbase may not exceed 136 inches. Anything over the limit must be the factory wheelbase measurement for the body being used.
4. Suspension may be blocked or solid.
5. No hydraulic suspension or air bags.

Transfer Case

1. Must be 1 ton or less.

2. 205 quick change is permitted.

3. No drop box allowed.

Hitch

1. Hitch must be rigid in all directions.

2. From point of hook to centerline of rear axle shall be no less than 27% of the wheelbase.

3. Hitch height may not exceed 26" high and hole in the hitch must be 3.75" x 3.0 opening.

4. No part of the hitch can exceed more than 4" above the frame rail and no further forward than the centerline of the rear axle.

5. Tab must be welded at the center of the rear end to assist in measuring the percentage of wheel base to hook point.

6. No vertical hitches. All hitches must be no steeper than 33 degrees.

Tires

1. Must be DOT approved 36" x 14.50 maximum.

2. Must have factory tire stamp for verification.

3. If the size is removed, they will be considered illegal.

4. No studded tires, chains or alterations allowed.

5. No dual tires.

Fuel

1. Gasoline/race fuel only.

2. No alcohol, nitrous, or power adders allowed.
3. Fuel tanks may be mounted on front of weight box.

Weight

1. 6,500 lbs. maximum.
2. Hanging weights and brackets may not exceed more than 195 inches from the centerline of rear axle but weight may not extend more than 65 inches from the centerline of the front axle.
3. No weight allowed in the cab.
4. All weight must be securely fastened.

Transmission

1. Must have blow proof bell housing on trucks with standard transmission.
2. Automatic transmissions must have a blow proof blanket.

Battery

1. Batteries are not allowed in the cab unless factory installed.
2. A manual batter disconnect easily accessible and clearly marked is required.

Body

1. Full fiberglass bodies are not permitted.
2. Must have a fire wall.
3. Bed floor is not required.
4. No flat beds. Bed must be OEM appearing.

5. If truck doesn't have a bed floor, there must be a cover on the bed.
6. No mud flap or dirt deflector allowed.
7. Maximum width of truck is 102".

Brakes

1. Must have working front brakes.
2. No traction control devices allowed.

Exhaust

1. Open headers permitted.
2. All vehicles must be equipped with upward pointing exhaust out of the hood or downward run under the fender.

Safety

1. All vehicles must have a working kill switch.
2. Must have drive shaft loops.
3. All fans must be shrouded at least 180 degrees on top.
4. All trucks must have a fully functioning fire extinguisher in the cab.
5. All drivers must wear a helmet, pants, and leather shoes/boots. Full fire suit is highly recommended.